



flexiform  
freestor tambour system



Freestor tambours have a range of internal components to tailor units to staff needs. Our storage surveys analyse the type, components and quantity each department requires, specifying units to save space and money.

# ds | ergonomics

ds-ergonomics.com

CREATING EFFECTIVE WORKING ENVIRONMENTS

## freestor tambour



Freestor tambour wardrobe with ventilated back.

Freestor tambours have a compact footprint and large storage capacity. The doors curl up within the unit creating a small operating area and have our widest range of components to tailor the units to each staff's needs.

### FEATURES & BENEFITS

- Easy grip inset handle with magnetic aluminium slam rail.
- Doors curl up into the unit giving full access to the unit.
- Fully welded carcass for exceptional rigidity and stiffness with no joins in the carcass to front or side elevations.
- Floor levelling.
- 15mm steel top or 25mm MFC top with 2mm ABS edging
- 2-point locking Lowe and Fletcher lock type 5689-2.
- 12.7mm slot centres to fit adjustable internal components.
- Components include plain shelf, slotted shelf, pigeon hole, lateral plain shelf with fixed suspension rails, lateral suspended filing rails, coat rail with shelf, pull out shelf, pull out filing frame with 2 adjustable rails, long rail A4 suspended rails, single drawer, 8" or 11" system drawers (see back of brochure for details).
- Optional acoustic perforated shutters allowing acoustic waves to enter and be absorbed with sound absorption EN ISO 11654:1997, acoustic absorption class C, NRC value 0.8, M3 fire rating.
- Extra deep tambour wardrobe with coat rail, shelf and ventilated back.

### SPECIFICATION

- Width options include 800mm, 825mm or 1000mm
- Height options include 695mm, 715mm, 720mm, 740mm, 1017mm, 1090mm, 1110mm, 1200mm, 1322mm, 1490mm, 1677mm or 2007mm
- Acoustic tambours are available in 1110mm, 1200mm, 1322mm and 2007mm
- Depth: 475mm as standard. Wardrobe 600mm
- 94% recyclable (based on a standard tambour)

